

AsReader®

ASR-03xD (UHF RFID)



Model Name		ASR-030D	ASR-030D-V2,V3,V4	ASR-031D	ASR-031D-V4
RFID	Spec	ISO 18000-63 (Formerly known as: ISO 18000-6 Type C)/EPC Class1 Gen2			
	Bandwidth	902 - 928MHz		865.6 - 867.6MHz	
	Output power	316mW(25dBm)	500mW(27dBm)	316mW(25dBm)	500mW(27dBm)
	Reading distance	~118inch(~3m) (*1)		~79inch(~2m) (*1)	
	Polarization characteristics	Circularly Polarized Antenna (internal)			
	Function	Read / Write / Lock / Kill			
Power source	Battery capacity	Built-in rechargeable lithium-ion battery (700mAh)			
	Continuous operation time	5 hours or more (*2)			
	Charging method	Magnetic charging cable (*3)			
	Charging time	About 2 hours (built-in battery) (*4)			
Key input		2 trigger key			
Communication	Interface	MFi on Lightning® (*5)			
Appearance	Dimensions (W)x(D)x(H)	2.51 × 0.38 × 4.61inch(63.7 × 9.7 × 117.2mm) (*6)			
	Weight (with battery)	About 80g			
	Material	PC			
	Casing color	White			
	LED display	Non-blinking Blue LED: Connected with device Blinking Blue LED: Reading RFID tags. Non-blinking Red LED: Battery is charging. Faint Red LED: Battery is fully charged			
Environment	Operating temperature	-10~45 °C, 20~85 % RH (Charge 0 °C or more, however)			
	Storage temperature	-20~60 °C, 10~95% RH			
	IP Rating	IP54 compliance			
	Anti-drop	(Six-sided * 4 edge, once each) 59.06 inch(1.5m) (*7)			
Certificate		Apple Mfi/FCC/RoHS		Apple Mfi/CE/RoHS	
Bundled items		Magnetic charging cable / manual			

*1 Differs per IC tag type and operating circumstances.

*2 The continuous reading time length by using our special app with Output power 24dBm, On time 100ms, Off time 400ms.

*3 Standard iPhone 2A charger is strongly recommendd to be used when using Magnetic charging cable .

*4 iPhone and AsReader batteries will charge simultaneously. iPhone and AsReader batteries will be recharged in 3.5 hrs and 2 hrs respectively in simultaneous recharging mode.

*5 SDK is available for free download.

*6 Excluding protrusions

*7 Depending on the drop angle, the iPhone® screen may break.

• For the latest information, please visit our website. · iPhone®, iPod touch® and Lightning® are trademarks of Apple Inc., registered in the U.S. and other countries.

· AsReader® is a registered trademark of Asterisk Inc. · All other trademarks are property of their respective owners.

<https://AsReader.com>

AsReader, Inc. U.S. Head Sales Office 920 SW 6th Ave., Ste 1200, Portland, OR 97204-1212 USA Tel: +1 (503) 770 2777

AsReader Europa B.V. Stationsplein 45, A4.004, 3013 AK Rotterdam, The Netherlands Tel: +31 (0) 10 808 0488

Dalian Mingrixing Technology Co., Ltd. R901, Heyi Building, No.6, Aixian Street, Dalian High-tech Industrial Zone, 116023, P. R. China Tel: +86 (0) 411 8445 8656

Asterisk Inc. Shin-Osaka Dainichi Bldg. 201, 5-6-16 Nishinakajima, Yodogawa-ku, Osaka-city, 532-0011, Japan Tel: +81 (0) 50 5536 1185