

## AsReader (ASR-P31N) Product Data Sheet

# AsReader®

## AsReader (ASR-P31N) RFID



Model Name		ASR-P31N
RFID	Spec	ISO 18000-63 (Old 18000-6C) / EPCglobal Class 1 Gen 2
	Bandwidth	920.6 MHz to 923.0 MHz (JP) 917.10 MHz to 926.90 MHz (US) 865.70 MHz to 867.50 MHz (EU)
	Output power	Max 27 dBm (US, EU)    Max 23 dBm (JP)
	Antenna port	SMA Jack 8 ports
	Functions	Read/Write/Lock/Kill
Power source		POE(IEEE 802.3af Class 0) or DC 12V 2A
Communication	Interface	USB or Ethernet (TCP/IP)
Appearance	Dimensions (W)x(D)x(H)	230*127*30mm (9.06*5*1.18 inch)
	Weight (with battery)	800g
	Materials	Steel
	Casing color	Black
	LED display	Power supply/Communication/RFID
Environment	Operating temperature	-10~+45°C
	Storage temperature	-20~+60°C
Certificates		TELEC    FCC (Planned)    CE (Planned)
Supported software		Windows(USB Connection only), iOS(TCP/IP Connection only), Android(Planned)

<https://AsReader.com>

AsReader, Inc. U.S. Head Sales Office 700 SW 5th Ave., Suite 4000, 3rd Fl., Portland, OR 97204-2000 U.S.A. Tel: +1 (503) 770 2777  
 AsReader Europe B.V. Stationsplein 45, A4.004, 3013 AK Rotterdam, The Netherlands Tel: +31 (0) 10 808 0488  
 Dalian Mingrixing Technology Co., Ltd. R901, Heyi Building, No.6, Aixian Street, Dalian High-tech Industrial Zone, 116023, P. R. China Tel: +86 (0) 411 8445 8656  
 Asterisk Inc. Shin-Osaka Dainichi Bldg. 201, 5-6-16 Nishinakajima, Yodogawa-ku, Osaka-city, 532-0011, Japan Tel: +81 (0) 50 5536 1185