

AsReader (ASR-P51N) Product Data Sheet

AsReader®

AsReader (ASR-P51N) RFID



Model Name		ASR-P51N
RFID	Spec	ISO 18000-63 (Old 18000-6C) / EPCglobal Class 1 Gen 2
	Bandwidth	916 MHz to 924 MHz (JP) 902 MHz to 928 MHz (US) 865 MHz to 868 MHz (EU)
	Output power	MAX 30dBm
	Antenna port	SMA Jack 4 ports
	Functions	Read / Write / Lock / Kill
Power source		POE(IEEE 802.3af Class 0) or DC 12V 2A
Communication	Interface	USB or Ethernet (TCP/IP)
Appearance	Dimensions (W)x(D)x(H)	230*127*30*mm (9.06*5*1.18 inch)
	Weight (with battery)	800g
	Materials	Aluminum
	Casing color	Black
	LED display	Power supply / Communication / RFID
Environment	Operating temperature	-10~+45°C
	Storage temperature	-20~+60°C
Certificates		TELEC/FCC/CE
Supported software		Windows, iOS(TCP/IP Connection only), Android(Planned)

<https://AsReader.com>

AsReader, Inc. U.S. Head Sales Office 920 SW 6th Ave., Ste 1200, Portland, OR 97204-1212 USA Tel: +1 (503) 770 2777
 AsReader Europa B.V. Stationsplein 45, A4.004, 3013 AK Rotterdam, The Netherlands Tel: +31 (0) 10 808 0488
 Dalian Mingrixing Technology Co., Ltd. R901, Heyi Building, No.6, Aixian Street, Dalian High-tech Industrial Zone, 116023, P.R. China Tel: +86 (0) 411 8445 8656
 Asterisk Inc. Shin-Osaka Dainichi Bldg. 201, 5-6-16 Nishinakajima, Yodogawa-ku, Osaka-city, 532-0011, Japan Tel: +81 (0) 50 5536 1185