



ASR-R250G-xxC (Barcode and UHF RFID)



Model Name		ASR-R250G-22/23C	ASR-R250G-02/03C	
RFID	Spec	ISO 18000-63 (Formerly known as: ISO 18000-6 Type C) / EPC Class1 Gen2		
	Bandwidth	902 - 928Mhz / 865 - 868Mhz		
	Output power	1W (30dBm) 5dBm~30dBm: adjustable per 1dBm		
	Reading distance	0 to 9.8 ft. (0 to 3m) or more *1		
	Polarization characteristics	Circular		
Function		Read / Write / Lock / Kill		
Barcode	Scan Engine	CMOS Sensor	—	
	Reading range	Barcode density	Distance from scanner	—
		100% U.P.C.	46 - 419 mm (1.8 - 16.5")	—
		5 mil Code 39	64 - 163 mm (2.5 - 6.5")	
		10 mil Code 39	28 - 338 mm (1.1 - 13.3")	
		6.7 mil PDF417	46 - 185 mm (1.8 - 7.3")	
10 mil Data Matrix	53 - 203 mm (2.1 - 8.0")			
Reading width	42.4° (horizontal), 33° (vertical)		—	
Reading angle	Pitch: ±45° Roll: 360° Skew motion: ±60° *2		—	
Reading code	<ul style="list-style-type: none"> • 1D: UPC/EAN/JAN, GS1 DataBar, Code 39, Code 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Code 2 of 5, MSI, Telepen, Trioptic, China Post • 2D Stacked: PDF417, MicroPDF417, GS1 Composite • 2D Matrix: Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Han Xin Code • Postal: Intelligent Mail Barcode, Postal-4i, Australian Post, British Post, Canadian Post, Japanese Post, Netherlands (KIX) Post, Postnet, Planet Code • OCR Option: OCR-A, OCR-B, E13B (MICR) 		—	
Light sources	Illumination: White LED, Aiming: Red Laser (Class 2)		—	
Power Source	Battery Capacity	Rechargeable lithium-ion battery 2600mAh		
	Continuous operation time	<ul style="list-style-type: none"> • Barcode Every 10 sec: about 17 hours (about 6,000 times) Every 5 sec: about 13 hours (about 9,000 times) 	<ul style="list-style-type: none"> • RFID 5 Sec Reading 30 Sec Waiting: about 9 hours (about 900 times) 10 Sec Reading 30 Sec Waiting: about 5 hours (about 400 times) 	
	Power Source	Magconn™ *3, MicroUSB		
	Charging time	About 4 hours (Built-in battery) *4		
Key input		Trigger, Mode, Power, Reset		
Communication	Interface USB			
Appearance	Dimensions (W) x (D) x (H)	129.7 * 76.8 * 150.9 mm (5.11 * 3.02 * 5.94 inch)		
	Weight (with Battery)	334g	327.5g	
	Material	PC		
	Casing color	White/Gray		
LED	Blue LED: Switch ON / Blinking Blue LED: Reading / Red LED: Battery is charging / Faint Red LED or LED is OFF: Battery is fully charged			
Environment	Operating environment	32° ~ 95°F (0° ~ 35°C)		
	Charge environment	32° ~ 113°F (0° ~ 45°C)		
	Storage environment	-4° ~ 140°F (-20° ~ 60°C)		
	IP Rating	IP54 compliance		
Anti-drop	(All 6-sides, twice each) 4 ft. (1.5m) *5			
Certificates	TELEC / FCC / CE / PSE (battery)			
Bundled items	microUSB cable / User manual			

*1 Differs per IC tag type and operating circumstances. *2 Differs per barcode type. *3 An AC adapter with an output of 5V 2A is strongly recommended for the Magconn™ cable.
 *4 The battery in the reader is charged first and then the connected smart device is charged next. *5 Reader only. Not including smartphone.
 •AsReader® is a registered trademark of Asterisk Inc. •All other trademarks are property of their respective owners

<https://AsReader.com>